



Intel Atom® Processor E3900 and A3900 Series

Datasheet Addendum

July 2019

Revision 004



You may not use or facilitate the use of this document in connection with any infringement or other legal analysis concerning Intel products described herein. You agree to grant Intel a non-exclusive, royalty-free license to any patent claim thereafter drafted which includes subject matter disclosed herein.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

All information provided here is subject to change without notice. Contact your Intel representative to obtain the latest Intel product specifications and roadmaps.

The products described may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Copies of documents which have an order number and are referenced in this document may be obtained by calling 1-800-548-4725 or by visiting: <http://www.intel.com/design/literature.htm>.

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software or service activation. Performance varies depending on system configuration. No computer system can be absolutely secure. Check with your system manufacturer or retailer or learn more at <http://www.intel.com/>

No computer system can be absolutely secure.

Intel, Intel Atom, Pentium, Celeron and the Intel logo are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2019, Intel Corporation. All rights reserved.



Contents

1.0	Introduction	6
1.1	SKU List.....	10
1.2	Processor Block Diagram	15
1.3	Terminology	16
1.4	Reference Documents.....	17
2.0	Physical Interfaces.....	18
2.1	PCI Device ID	18
2.2	Memory Interface Signals.....	19
2.3	SDIO Interface Signals.....	19
2.4	High-Speed Universal Asynchronous Receiver/Transmitter (UART) Interface Signals.....	20
2.5	Audio Interface Signals	21
2.6	Serial I/O (SIO) (LPSS) SPI Signals.....	24
2.7	GPIO Multiplexing.....	26
2.8	RTC Signals.....	27
2.9	Other Signals.....	27
3.0	Functional Description	28
3.1	Processor Core Overview	28
3.2	System Memory Controller	29
3.2.1	Supported Memory Overview.....	29
3.2.2	Memory Configurations	30
3.3	SDIO	30
3.4	Audio Controller.....	31
3.5	Serial I/O (SIO) (LPSS).....	31
3.6	Clocking.....	32
3.7	Spread Spectrum Clocking for EMI mitigation	33
3.8	Other Interfaces.....	33
4.0	Electrical Specifications.....	34
4.1	Voltage and Current Specifications.....	34
4.2	SDIO DC Specifications	35
5.0	Ball Map, Processor Pin Locations, and Package Information	38
5.1	Package Mechanical Drawing: Apollo Lake-I ¹	40



Figures

Figure 1.	Processor Block Diagram	15
Figure 2.	CPU L2 Cache Structure (Dual Core).....	28
Figure 3.	CPU L2 Cache Structure (Quad Core).....	28
Figure 4.	Package Mechanical Drawing: Apollo Lake-I ¹ (1 of 2)	40
Figure 5.	Package Mechanical Drawing: Apollo Lake-I ¹ (2 of 2)	41

Tables

Table 1.	Intel Atom® Processor E3900 and A3900 Series Features	6
Table 2.	Intel Atom® E3900 Processor Series (D-0 stepping) SKU List.....	10
Table 3.	Intel Atom® E3900 Processor Series (F-1 stepping) SKU List.....	10
Table 4.	Intel Atom® A3900 Processor Series (D-0 stepping) SKU List	11
Table 5.	Intel Atom® A3900 Processor Series (F-1 stepping) SKU List	13
Table 6.	Terminology	16
Table 7.	Reference Documents	17
Table 8.	PCI Configuration Matrix	18
Table 9.	DDR3L ECC System Memory Signals.....	19
Table 10.	SDIO Interface Signals.....	19
Table 11.	UART Interface Signals.....	20
Table 12.	Audio Interface Signals	21
Table 13.	SIO (LPSS) SPI Signals	24
Table 14.	GPIO Multiplexing.....	26
Table 15.	RTC Signals.....	27
Table 16.	Supported Memory Technologies	29
Table 17.	SDIO Features	30
Table 18.	SDIO Working Modes.....	30
Table 19.	Audio Controller Features	31
Table 20.	I/O Supported Interfaces.....	31
Table 21.	Summary of Clock Signals	32
Table 22.	Power Rail DC Specifications and ICCMAX Values.....	34
Table 23.	Intel Atom® Processor E3900 Series Vcc_VCGI Rail ICCMAX Values	35
Table 24.	Intel Atom® Processor A3900 Series Vcc_VCGI Rail ICCMAX Values	35
Table 25.	SDIO Signal Group DC Specifications	35
Table 26.	Signal Name Comparison between N- and J- Series Processors and E3900 and A3900 Series Processors.....	38



Revision History

Date	Revision	Description
July 2019	004	<ul style="list-style-type: none">• Updated Table 1, with Z-height value corrected from 2.426mm to 2.422mm• Updated Table 14, GPIO Multiplexing for Fn1-Fn4 signal
May 2019	003	<ul style="list-style-type: none">• Updated Table 1 for Graphics and Imaging Interface.• Added Table 3. Intel Atom® E3900 Processor Series (F-1 stepping) SKU List.• Added Table 5. Intel Atom® A3900 Processor Series (F-1 Stepping) SKU List.• Replaced Figure 1. Processor Block Diagram.• Added notes no.2 under Table 10.• Updated VCC-3P3C-A in Table 20.• Added Pin Number 'P57' in Table 24.
October 2018	002	<ul style="list-style-type: none">• Updated Table 1 with Still and Video column changed to Still Capture and Video Capture in Imaging (CSI D-PHY 1.1) and (CSI D-PHY 1.1).• Updated Table 2 by adding LPDDR4 frequency.• Updated Table 3 by adding A3920 SKU info and LPDDR4 frequency.• Updated Table 9 for GPIO_112 until GPIO_117 by adding (Fn2).• Added notes no. 5 under Table 9.• Updated Table 13 by adding Vil.• Changed Table 15 for Data Rate from 104 MB to 100 MB.• Updated Table 16 for SDR104.• Updated Table 19 for Storage – SDIO.• Changed section 3.7 from Time Coordinated Computing (TCC) to Spread Spectrum Clocking for EMI mitigation.• Updated Table 22 by adding A3920 SKU.• Added section 5.1 Package Mechanical Drawing.
July 2017	001	<ul style="list-style-type: none">• Initial release.

§



1.0 Introduction

This Datasheet Addendum is a supplement to the Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3 (Document Number: 334817). This addendum contains additional information pertinent to the implementation and operation of the Intel Atom® processor E3900 and A3900 series.

The processor is the Intel® architecture processor that integrates the next-generation Intel processor core, graphics, memory controller, and I/O interfaces into a single system-on-chip solution.

Register information for the Intel Atom® processor E3900 and A3900 series is the same as that of the N- and J- Series Processors. Refer to Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 2 of 3 (Document Number: 334818) and Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 3 of 3 (Document Number: 334819).

Table 1. Intel Atom® Processor E3900 and A3900 Series Features

Interface	Category	Intel Atom® Processor E3900 and A3900 Series
CPU	Number of Cores	Refer to Table 2 and Table 4 for details
	Burst Speed	Refer to Table 2 and Table 4 for details
	LFM/HFM	Refer to Table 2 and Table 4 for details
	Junction Temperature T _j	-40°C to 110°C
	Temperature T _c ase (E3930)	-40°C to 103°C
	Temperature T _c ase (E3940)	-40°C to 100°C
	Temperature T _c ase (E3950)	-40°C to 98°C
	Temperature T _c ase (A3930)	-40°C to 103°C
	Temperature T _c ase (A3940)	-40°C to 101°C
	Temperature T _c ase (A3950)	-40°C to 100°C
	Temperature T _c ase (A3960)	-40°C to 98°C

Introduction



Interface	Category	Intel Atom® Processor E3900 and A3900 Series
Package	Type	Same as the N- and J- Series Processors
	I/O Count	Same as the N- and J- Series Processors
	Ball Count	Same as the N- and J- Series Processors
	Minimum Ball Pitch	Same as the N- and J- Series Processors
	Z-height (Pre-SMT)	2.422 mm ±0.113 mm
	Integrated Heat Spreader	Yes
Graphics	Generation	Same as the N- and J- Series Processors
	Frequency	Refer to Table 2 and Table 4 for details
	Execution Units	Refer to Table 2 and Table 4 for details
Display	MIPI*-DSI Ports	Same as the N- and J- Series Processors
	Maximum MIPI*-DSI Resolution	Same as the N- and J- Series Processors
	Maximum DSI Data Rate	Same as the N- and J- Series Processors
	DDI Ports (External)	Same as the N- and J- Series Processors
	Maximum DDI (External) Resolution	Same as the N- and J- Series Processors
	Embedded DisplayPort* (eDP*) Ports	Same as the N- and J- Series Processors
	Maximum eDP Resolution	Same as the N- and J- Series Processors
	Maximum DDI Data Rate	Same as the N- and J- Series Processors
Memory	Interface	Up to 2x64 DDR3L (Non-ECC) Up to 2x72 DDR3L (ECC) Up to 4x32 Low-Power Double Data Rate memory technology (LPDDR4) (non-ECC)
	Supported Transfer Data Rates (MT/s)	DDR3L: Same as the N- and J- Series Processors



Interface	Category	Intel Atom® Processor E3900 and A3900 Series
		DDR3L ECC: 1333/1600 MT/s LPDDR4: Same as the N- and J- Series Processors
Imaging (CSI D-PHY 1.1)	Number of Lanes	Same as the N- and J- Series Processors
	Speed	Same as the N- and J- Series Processors
	Still Capture	Same as the N- and J- Series Processors
	Video Capture	4096 x 2160 @ 30fps (For E0 & F1 steppings only)
	Video HDR	Same as the N- and J- Series Processors
	Maximum Vector Unit	Same as the N- and J- Series Processors
Imaging (CSI D-PHY 1.2)	Number of Lanes	Same as the N- and J- Series Processors
	Speed	Same as the N- and J- Series Processors
	Still Capture	Same as the N- and J- Series Processors
	Video Capture	4096 x 2160 @ 30fps (For E0 & F1 steppings only)
	Video HDR	Same as the N- and J- Series Processors
	Maximum Vector Unit	Same as the N- and J- Series Processors
Audio	Number of Ports	6x I ² S 4x DMIC 1x HD Audio (HDA/mHDA Codec)
	Maximum I ² S* Speed	Same as the N- and J- Series Processors
USB	SuperSpeed USB (USB 3.0) Ports	Same as the N- and J- Series Processors
	Maximum USB 3.0 Speed	Same as the N- and J- Series Processors
	USB 2.0 Ports	Same as the N- and J- Series Processors
	Maximum USB 2.0 Speed	Same as the N- and J- Series Processors
PCI Express* (PCIe*) Gen2	Number of Ports	Same as the N- and J- Series Processors
	Maximum Speed	Same as the N- and J- Series Processors
Serial ATA* (SATA*) Gen3	Number of Ports	Same as the N- and J- Series Processors
	Maximum Speed	Same as the N- and J- Series Processors



Interface	Category	Intel Atom® Processor E3900 and A3900 Series
Storage	SD* Card	Same as the N- and J- Series Processors
	Maximum SD Card Speed	Same as the N- and J- Series Processors
	eMMC*	Same as the N- and J- Series Processors
	Maximum eMMC Speed	Same as the N- and J- Series Processors
	Secure Digital I/O (SDIO)	1 port
	Maximum SDIO Speed	UHS-I at SDR 104/50/25/12 and DDR50
Low-Power Subsystem (LPSS)	I ² C* Ports	Same as the N- and J- Series Processors
	Maximum I ² C Speed	Same as the N- and J- Series Processors
	High-Speed UART (HSUART) (Maximum)	4 [1x Discrete GNSS (UART1), 1x Host OS Debug (UART2) and 2x Generic (UART0 and 3)]
	Maximum HUART Speed	Same as the N- and J- Series Processors
	Serial Peripheral Interface (SPI) (Maximum)	Controller: 3 Devices supported: 7
	Maximum SPI Speed	Same as the N- and J- Series Processors
Integrated Sensor Hub (ISH)	I ² C	Same as the N- and J- Series Processors
	Maximum I ² C Speed	Same as the N- and J- Series Processors
	GPIO	Same as the N- and J- Series Processors
Intel Legacy Block (iLB)	Fast SPI	Same as the N- and J- Series Processors
	Maximum Fast SPI Frequency	Same as the N- and J- Series Processors
Power Management Controller (PMC)	I ² C (PMIC)	Same as the N- and J- Series Processors
	Maximum I ² C Speed	Same as the N- and J- Series Processors
Low Pin Count (LPC)	Number of Ports	Same as the N- and J- Series Processors
	Maximum Speed	Same as the N- and J- Series Processors
System Management Bus (SMBus)	Number of Ports	Same as the N- and J- Series Processors
	Maximum Speed	Same as the N- and J- Series Processors

NOTE: Depending on Stock Keeping Unit (SKU).



1.1 SKU List

Table 2. Intel Atom® E3900 Processor Series (D-0 stepping) SKU List

	Intel Atom® x5 E3930	Intel Atom® x5 E3940	Intel Atom® x7 E3950
SSPEC	R33Q	R33M	R33P
MM#	953086	953083	953085
Stepping	D-0	D-0	D-0
No. of Cores	2	4	4
Processor Frequency LFM/HFM/ Burst	800 MHz / 1.3 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 2.0 GHz
Graphics Frequency LFM/HFM/ Burst	100 MHz / 400 MHz / 550 MHz	100 MHz / 400 MHz / 600 MHz	100 MHz / 500 MHz / 650 MHz
ISP Frequency Low/High/Burst	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 700 MHz
GFX Industrial Reliability Frequency	400 MHz	400 MHz	400 MHz
GFX EU	12	12	18
TDP (W) at TjMax	6.5	9.5	12
SOi3 Power (mW) at 30°C	15	15	18
S3 Power (mW) at 30°C	13	13	16
S5 Power (mW) at 30°C	13	13	16
DDR3L ECC Option	Yes	Yes	Yes
LPDDR4 Frequency	up to 2133 MT/s	up to 2133 MT/s	up to 2400 MT/s

Table 3. Intel Atom® E3900 Processor Series (F-1 stepping) SKU List

	Intel Atom® x5 E3930	Intel Atom® x5 E3940	Intel Atom® x7 E3950
SSPEC/QDF	REKA	REK6	REK9
MM#	983202	983195	983200
Stepping	F-1	F-1	F-1
No. of Cores	2	4	4
Processor Frequency LFM/HFM/ Burst	800 MHz / 1.3 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 2.0 GHz

Introduction



	Intel Atom® x5 E3930	Intel Atom® x5 E3940	Intel Atom® x7 E3950
Graphics Frequency LFM/HFM/ Burst	100 MHz / 400 MHz / 550 MHz	100 MHz / 400 MHz / 600 MHz	100 MHz / 500 MHz / 650 MHz
ISP Frequency Low/High/Burst	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 700 MHz
GFX Industrial Reliability Frequency	400 MHz	400 MHz	400 MHz
GFX EU	12	12	18
TDP (W) at TjMax	6.5	9.5	12
S0i3 Power (mW) at 30°C	15	15	18
S3 Power (mW) at 30°C	13	13	16
S5 Power (mW) at 30°C	13	13	16
DDR3L ECC Option	Yes	Yes	Yes
LPDDR4 Frequency	up to 2133 MT/s	up to 2133 MT/s	up to 2400 MT/s

Table 4. Intel Atom® A3900 Processor Series (D-0 stepping) SKU List

	Intel Atom® x7 A3920	Intel Atom® x5 A3930	Intel Atom® x5 A3940	Intel Atom® x7 A3950	Intel Atom® x7 A3960
SSPEC	REJZ	R33R	R33L	R33N	R33U
MM#	953085	953087	953082	953084	953096
Stepping	D-0	D-0	D-0	D-0	D-0
No. of Cores	4	2	4	4	4
Processor Frequency LFM/HFM/ Burst	800 MHz / 1.6 GHz / 2.08 GHz	800 MHz / 1.3 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 2.0 GHz	800 MHz / 1.9 GHz / 2.4 GHz
Graphics Frequency LFM/HFM/ Burst	100 MHz / 500 MHz / 650 MHz	100 MHz / 400 MHz / 550 MHz	100 MHz / 400 MHz / 600 MHz	100 MHz / 500 MHz / 650 MHz	100 MHz / 600 MHz / 750 MHz
ISP Frequency Low/High/Burst	200 MHz / 550 MHz / 700 MHz	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 700 MHz	200 MHz / 550 MHz / 700 MHz
GFX Industrial Reliability Frequency	400 MHz	NA	NA	NA	NA
GFX EU	18	12	12	18	18
TDP (W) at TjMax	12	6	8	9.5	12.5
S0i3 Power (mW) at 30°C	18	15	15	18	18



	Intel Atom® x7 A3920	Intel Atom® x5 A3930	Intel Atom® x5 A3940	Intel Atom® x7 A3950	Intel Atom® x7 A3960
S3 Power (mW) at 30°C	16	13	13	16	12
S5 Power (mW) at 30°C	16	13	13	16	12
DDR3L ECC Option	No	No	No	No	No
AEC-Q100 Qualification	No	Yes	Yes	Yes	Yes
LPDDR4 Frequency	up to 2400 MT/s	up to 2133 MT/s	up to 2133 MT/s	up to 2400 MT/s	up to 2400 MT/s

NOTES:

1. Intel Atom® processor A3900 series are for automotive customers only. No support for non-automotive customers.
2. Intel Atom® A3900 Processor Series (D-0 stepping) SKU List for Tray Pack.

	Intel Atom® x5 A3930	Intel Atom® x5 A3940	Intel Atom® x7 A3950	Intel Atom® x7 A3960
SSPEC	R3VK	R3VH	R3VJ	R3VL
MM#	962843	96284 1	962842	96284 4
Tray / T&R	T&R	T&R	T&R	T&R
Stepping	D-0	D-0	D-0	D-0
No. of Cores	2	4	4	4
Processor Frequency LFM/HFM/ Burst	800 MHz / 1.3 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 2.0 GHz	800 MHz / 1.9 GHz / 2.4 GHz
Graphics Frequency LFM/HFM/ Burst	100 MHz / 400 MHz / 550 MHz	100 MHz / 400 MHz / 600 MHz	100 MHz / 500 MHz / 650 MHz	100 MHz / 600 MHz / 750 MHz
ISP Frequency Low/High/Burst	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 700 MHz	200 MHz / 550 MHz / 700 MHz
GFX Industrial Reliability Frequency	NA	NA	NA	NA
GFX EU	12	12	18	18
TDP (W) at TjMax	6	8	9.5	12.5
SOi3 Power (mW) at 30°C	15	15	18	18
S3 Power (mW) at 30°C	13	13	16	12
S5 Power (mW) at 30°C	13	13	16	12
DDR3L ECC Option	No	No	No	No



	Intel Atom® x5 A3930	Intel Atom® x5 A3940	Intel Atom® x7 A3950	Intel Atom® x7 A3960
AEC-Q100 Qualification	Yes	Yes	Yes	Yes
LPDDR4 Frequency	up to 2133 MT/s	up to 2133 MT/s	up to 2400 MT/s	up to 2400 MT/s

NOTE: Intel Atom® Processor A3900 series (D-0 stepping) SKU List for Tape & Reel Pack.

Table 5. Intel Atom® A3900 Processor Series (F-1 stepping) SKU List

	Intel Atom® x5 A3930	Intel Atom® x5 A3940	Intel Atom® x7 A3950	Intel Atom® x7 A3960
SSPEC	REKC	REK4	REK7	REKE
MM#	983207	983193	983198	983210
Stepping	F-1	F-1	F-1	F-1
No. of Cores	2	4	4	4
Processor Frequency LFM/HFM/ Burst	800 MHz / 1.3 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 2.0 GHz	800 MHz / 1.9 GHz / 2.4 GHz
Graphics Frequency LFM/HFM/ Burst	100 MHz / 400 MHz / 550 MHz	100 MHz / 400 MHz / 600 MHz	100 MHz / 500 MHz / 650 MHz	100 MHz / 600 MHz / 750 MHz
ISP Frequency Low/High/Burst	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 700 MHz	200 MHz / 550 MHz / 700 MHz
GFX EU	12	12	18	18
TDP (W) at TjMax	6	8	9.5	12.5
S0i3 Power (mW) at 30°C	15	15	18	18
S3 Power (mW) at 30°C	13	13	16	12
S5 Power (mW) at 30°C	13	13	16	12
DDR3L ECC Option	No	No	No	No
AEC-Q100 Qualification	Yes	Yes	Yes	Yes
LPDDR4 Frequency	up to 2133 MT/s	up to 2133 MT/s	up to 2400 MT/s	up to 2400 MT/s

NOTE: Intel Atom® A3900 Processor Series (F-1 stepping) SKU List for Tray Pack.



Introduction

	Intel Atom® x5 A3930	Intel Atom® x5 A3940	Intel Atom® x7 A3950	Intel Atom® x7 A3960
SSPEC	REKD	REK5	REK8	REKF
MM#	983208 4	98319 4	983199	98321 1
Tray / T&R	T&R	T&R	T&R	T&R
Stepping	F-1	F-1	F-1	F-1
No. of Cores	2	4	4	4
Processor Frequency LFM/HFM/ Burst	800 MHz / 1.3 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 1.8 GHz	800 MHz / 1.6 GHz / 2.0 GHz	800 MHz / 1.9 GHz / 2.4 GHz
Graphics Frequency LFM/HFM/ Burst	100 MHz / 400 MHz / 550 MHz	100 MHz / 400 MHz / 600 MHz	100 MHz / 500 MHz / 650 MHz	100 MHz / 600 MHz / 750 MHz
ISP Frequency Low/High/ Burst	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 675 MHz	200 MHz / 550 MHz / 700 MHz	200 MHz / 550 MHz / 700 MHz
GFX EU	12	12	18	18
TDP (W) at TjMax	6	8	9.5	12.5
S0i3 Power (mW) at 30°C	15	15	18	18
S3 Power (mW) at 30°C	13	13	16	12
S5 Power (mW) at 30°C	13	13	16	12
DDR3L ECC Option	No	No	No	No
AEC-Q100 Qualification	Yes	Yes	Yes	Yes
LPDDR4 Frequency	up to 2133 MT/s	up to 2133 MT/s	up to 2400 MT/s	up to 2400 MT/s


NOTE: Intel Atom® Processor A3900 series (F-1 stepping) SKU List for Tape & Reel Pack



1.2

Processor Block Diagram

Figure 1. Processor Block Diagram





1.3 Terminology

Table 6. Terminology

Term	Description
DMIC	Digital Microphone
DQS	Data Strobe
ECC	Error Correcting Code
eDP*	Embedded DisplayPort
GNSS	Global Navigation Satellite System
HDMI*	High Definition Multimedia Interface
HSUART	High-Speed UART
iLB	Intel Legacy Block
LPC	Low Pin Count
LPDDR	Low-Power Double Data Rate memory
LPSS	Low-Power Subsystem
PCIe*	PCI Express*
PMC	Power Management Controller
PMIC	Power Management Integrated Circuit
RTC	Real Time Clock
SATA*	Serial ATA
SDIO	Secure Digital I/O
SDRAM	Synchronous Dynamic Random Access Memory
SIO	Serial I/O
SKU	Stock Keeping Unit
SMBus	System Management Bus
SPI	Serial Peripheral Interface
SSP	Synchronous Serial Protocol
UART	Universal Asynchronous Receiver/Transmitter



1.4 Reference Documents

Table 7. Reference Documents

Document	Document No./Location
<i>Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3</i>	334817
<i>Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 2 of 3</i>	334818
<i>Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 3 of 3</i>	334819
<i>Intel® Pentium® and Celeron® Processor N- and J- Series Specification Update</i>	334820
<i>Intel® 64 and IA-32 Architectures Software Developer's Manuals</i> <i>Volume 1: Basic Architecture</i> <i>Volume 2A: Instruction Set Reference, A-M</i> <i>Volume 2B: Instruction Set Reference, N-Z</i> <i>Volume 3A: System Programming Guide</i> <i>Volume 3B: System Programming Guide</i>	https://software.intel.com/en-us/articles/intel-sdm

§



2.0 Physical Interfaces

Many interfaces contain physical pins. These groups of pins make up the physical interfaces. Because of the large number of interfaces and the small size of the package, some interfaces share their pins with GPIOs, while others use dedicated physical pins. This chapter summarizes the physical interfaces, including the diversity in GPIO multiplexing options.

2.1 PCI Device ID

Table 8. PCI Configuration Matrix

Device ID	Device Description	Device	Function
0x5ABC	UART 0	24	0
0x5AEE	UART 3	24	3
0x5AC4	SPI 1	25	1
0x5AC6	SPI 2	25	2
0x5AD0	SDIO	30	0

NOTE: Other PCI Device IDs are the same as those of N- and J- Series Processors. Refer to Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3 (Document Number: 334817).



2.2 Memory Interface Signals

Table 9. DDR3L ECC System Memory Signals

Signal Name	Dir.	I/O Voltage	Type	Description
MEM_CH0_ECC_DQ[7:0] MEM_CH1_ECC_DQ[7:0]	I/O	VDDQ	DDR3L PHY	ECC Data Buses: Data signals interface to the Synchronous Dynamic Random Access Memory (SDRAM) data buses.
MEM_CH0_ECC_DQSP[8] MEM_CH0_ECC_DQSN[8] MEM_CH1_ECC_DQSP[8] MEM_CH1_ECC_DQSN[8]	I/O	VDDQ	DDR3L PHY	ECC Data Strobes (DQS): Differential data strobe pairs. The data is captured at the crossing point of DQS during read and write transactions.

NOTE: Signal names shown in this table are additional ECC signal names. The rest of the DDR3L signals are the same as those of N- and J- Series Processors.

2.3 SDIO Interface Signals

Table 10. SDIO Interface Signals

Signal Name	GPIO	Dir.	I/O Voltage	Type	Description
SDIO_CLK	GPIO_166	I/O	V1P8	GPIO	SDIO Clock: Port Clock.
SDIO_CMD	GPIO_171	I/O	V1P8	GPIO	SDIO Command: This signal is used for device initialization and transfer of commands.
SDIO_D0 SDIO_D1 SDIO_D2 SDIO_D3	GPIO_167 GPIO_168 GPIO_169 GPIO_170	I/O	V1P8	GPIO	SDIO Data Bits 0 to 3: Bidirectional ports used to transfer data to and from the SDIO device. By default, after power-up or reset, only D [0] is used for data transfer. A wider data bus can be configured for data transfer, using D [0]-D[3].
SDIO_PWR_DOWN_N	GPIO_183	I/O	V1P8	GPIO	SDIO Bus Power: Controls power for SDIO devices.



2.4

High-Speed Universal Asynchronous Receiver/Transmitter (UART) Interface Signals

Table 11. UART Interface Signals

Signal Name	GPIO#	Dir.	I/O Voltage	Type	Description
LPSS_UART0_RXD	GPIO_38	I	V1P8	GPIO	UART0 data input
LPSS_UART0_TXD	GPIO_39	O	V1P8	GPIO	UART0 data output
LPSS_UART0_RTS_N	GPIO_40	O	V1P8	GPIO	UART0 Ready to Send
LPSS_UART0_CTS_N	GPIO_41	I	V1P8	GPIO	UART0 Clear to Send
LPSS_UART1_RXD	GPIO_42	I	V1P8	GPIO	UART1 data input
LPSS_UART1_TXD	GPIO_43	O	V1P8	GPIO	UART1 data output
LPSS_UART1_RTS_N	GPIO_44	O	V1P8	GPIO	UART1 Ready to Send
LPSS_UART1_CTS_N	GPIO_45/GPIO1 53 (Fn 3)	I	V1P8	GPIO	UART1 Clear to Send
LPSS_UART2_RXD	GPIO_46/GPIO_150 (Fn 3)	I	V1P8	GPIO	UART2 data input
LPSS_UART2_TXD	GPIO_47/GPIO_151 (Fn 3)	O	V1P8	GPIO	UART2 data output
LPSS_UART2_RTS_N	GPIO_48/GPIO_152 (Fn3)	O	V1P8	GPIO	UART2 Ready to Send
LPSS_UART2_CTS_N	GPIO_49	I	V1P8	GPIO	UART2 Clear to Send
LPSS_UART3_RXD	GPIO_112 (Fn2)	I	V1P8	GPIO	UART3 data input
LPSS_UART3_TXD	GPIO_113 (Fn2)	O	V1P8	GPIO	UART3 data output
LPSS_UART3_RTS_N	GPIO_116 (Fn2)	O	V1P8	GPIO	UART3 Ready to Send



Signal Name	GPIO#	Dir.	I/O Voltage	Type	Description
LPSS_UART3_CTS_N	GPIO_117 (Fn2)	I	V1P8	GPIO	UART3 Clear to Send

NOTES:

1. The E3900 and A3900 Series Processors support four LPSS_UART ports, while the N- and J-Series Processors support only LPSS_UART [2:1] ports.
2. The LPSS_UART1 port is dedicated for discrete Global Navigation Satellite System (GNSS). This port can be used for generic UART functionality if GNSS is not used.
3. The LPSS_UART2 port is dedicated for host OS debug.
4. The LPSS_UART0 and LPSS_UART3 ports are for generic UART functionality.
5. Only UART [1:0] ports support DMA.

2.5 Audio Interface Signals

Table 12. Audio Interface Signals

Signal Name	GPIO#	Dir.	I/O Voltage	Type	Description
AVS_I2S1_MCLK	GPIO_74	O	V1P8	GPIO	MCLK for Master Mode operation or GPIO
AVS_I2S1_BCLK	GPIO_75	I/O	V1P8	GPIO	Analog microphone I ² S Bit Clock – bidirectional. In master mode, the BCLK is supplied by the processor; in slave mode, it serves as an input.
AVS_I2S1_WS_SYNC	GPIO_76	I/O	V1P8	GPIO	Word Select or SYNC input – marks the beginning of serial sample.
AVS_I2S1_SDI	GPIO_77	I	V1P8	GPIO	Analog microphone I ² S Data in – serial data input
AVS_I2S1_SDO	GPIO_78	I/O	V1P8	GPIO	Audio Codec I ² S Data out – serial data output
AVS_I2S2_MCLK	GPIO_84	O	V1P8	GPIO	MCLK for Master Mode operation or GPIO



Physical Interfaces

Signal Name	GPIO#	Dir.	I/O Voltage	Type	Description
AVS_I2S2_BCLK	GPIO_85	I/O	V1P8	GPIO	Analog microphone I ² S Bit Clock – bidirectional. In master mode, the BCLK is supplied by the processor; in slave mode, it serves as an input.
AVS_I2S2_WS_SYNC	GPIO_86	I/O	V1P8	GPIO	Word Select or SYNC input – marks the beginning of serial sample.
AVS_I2S2_SDI	GPIO_87	I	V1P8	GPIO	Analog microphone I ² S Data in – serial data input
AVS_I2S2_SDO	GPIO_88	I/O	V1P8	GPIO	Audio Codec I ² S Data out – serial data output
AVS_I2S3_BCLK	GPIO_89	I/O	V1P8	GPIO	Audio Codec I ² S Bit Clock – bidirectional. In master mode, the BCLK is supplied by the processor; in slave mode, it serves as an input.
AVS_I2S3_WS_SYNC	GPIO_90	I/O	V1P8	GPIO	Audio Codec frame synchronization or word select signal. Bidirectional – may be configured for master or slave.
AVS_I2S3_SDI	GPIO_91	I	V1P8	GPIO	Audio Codec I ² S Data in – serial data input
AVS_I2S3_SDO	GPIO_92	I/O	V1P8	GPIO	Audio Codec I ² S Data out – serial data output
AVS_I2S4_BCLK	GPIO_79	I/O	V1P8	GPIO	Audio Codec I ² S Bit Clock – bidirectional. In master mode, the BCLK is supplied by the processor; in slave mode, it serves as an input.

Physical Interfaces



Signal Name	GPIO#	Dir.	I/O Voltage	Type	Description
AVS_I2S4_WS_SYNC	GPIO_80	I/O	V1P8	GPIO	Audio Codec frame synchronization or word select signal. Bidirectional – may be configured for master or slave.
AVS_I2S4_SDI	GPIO_81	I	V1P8	GPIO	Audio Codec I ² S Data in – serial data input
AVS_I2S4_SDO	GPIO_82	I/O	V1P8	GPIO	Audio Codec I ² S Data out – serial data output
AVS_I2S5_BCLK	GPIO_150	I/O	V1P8	GPIO	Audio Codec I ² S Bit Clock – bidirectional. In master mode, the BCLK is supplied by the processor; in slave mode, it serves as an input.
AVS_I2S5_WS_SYNC	GPIO_151	I/O	V1P8	GPIO	Audio Codec frame synchronization or Word select signal. Bidirectional – may be configured for master or slave.
AVS_I2S5_SDI	GPIO_152	I	V1P8	GPIO	Audio Codec I ² S Data in – serial data input
AVS_I2S5_SDO	GPIO_153	I/O	V1P8	GPIO	Audio Codec I ² S Data out – serial data output
AVS_I2S6_BCLK	GPIO_146	I/O	V1P8	GPIO	Audio Codec I ² S Bit Clock – bidirectional. In master mode, the BCLK is supplied by the processor; in slave mode, it serves as an input.
AVS_I2S6_WS_SYNC	GPIO_147	I/O	V1P8	GPIO	Audio Codec frame synchronization or Word select signal. Bidirectional – may be configured for master or slave.
AVS_I2S6_SDI	GPIO_148	I	V1P8	GPIO	Audio Codec I ² S Data in – serial data input



Signal Name	GPIO#	Dir.	I/O Voltage	Type	Description
AVS_I2S6_SDO	GPIO_149	I/O	V1P8	GPIO	Audio Codec I ² S Data out – serial data output

NOTES:

1. The E3900 and A3900 Series Processors support six I²S interfaces, while the N- and J- Series Processors support only AVS_I2S2 and AVS_I2S6 interfaces.
2. I2S1_MCLK and I2S2_MCLK can be used respectively for I2S1 and I2S2 interface only.

2.6 Serial I/O (SIO) (LPSS) SPI Signals

Table 13. SIO (LPSS) SPI Signals

Signal Name	GPIO	Dir.	I/O Voltage	Type	Description
SIO_SPI_0_CLK	GPIO_104	I/O	V1P8	GPIO	SIO SPI 0 Clock: SPI Clock signal
SIO_SPI_0_FSO	GPIO_105	O	V1P8	GPIO	SIO SPI 0 Frame Select 0: Used as the SPI bus request signal
SIO_SPI_0_FS1	GPIO_106	O	V1P8	GPIO	SIO SPI 0 Frame Select 1: Used as the SPI bus request signal
SIO_SPI_0_RXD	GPIO_109	I	V1P8	GPIO	SIO SPI 0 Data Pad: Data Input pin for the processor
SIO_SPI_0_TXD	GPIO_110	O	V1P8	GPIO	SIO SPI 0 Data Pad: Data Output pin for the processor
SIO_SPI_1_CLK	GPIO_111	I/O	V1P8	GPIO	SIO SPI 1 Clock: SPI Clock signal
SIO_SPI_1_FSO	GPIO_112	O	V1P8	GPIO	SIO SPI 1 Frame Select 0: Used as the SPI bus request signal
SIO_SPI_1_FS1	GPIO_113	O	V1P8	GPIO	SIO SPI 1 Frame Select 1: Used as the SPI bus request signal
SIO_SPI_1_RXD	GPIO_116	I	V1P8	GPIO	SIO SPI 1 Data Pad: Data Input pin for the processor
SIO_SPI_1_TXD	GPIO_117	O	V1P8	GPIO	SIO SPI 1 Data Pad: Data Output pin for the processor
SIO_SPI_2_CLK	GPIO_118	I/O	V1P8	GPIO	SIO SPI 2 Clock: SPI Clock signal

Physical Interfaces



Signal Name	GPIO	Dir.	I/O Voltage	Type	Description
SIO_SPI_2_FSO	GPIO_119	O	V1P8	GPIO	SIO SPI 2 Frame Select 0: Used as the SPI bus request signal
SIO_SPI_2_FS1	GPIO_120	O	V1P8	GPIO	SIO SPI 2 Frame Select 1: Used as the SPI bus request signal
SIO_SPI_2_FS2	GPIO_121	O	V1P8	GPIO	SIO SPI 2 Frame Select 2: Used as the SPI bus request signal
SIO_SPI_2_RXD	GPIO_122	I	V1P8	GPIO	SIO SPI 2 Data Pad: Data Input pin for the processor
SIO_SPI_2_TXD	GPIO_123	O	V1P8	GPIO	SIO SPI 2 Data Pad: Data Output pin for the processor

NOTE: The E3900 and A3900 Series Processors support three SPI ports, while the N- and J- Series Processors support only the SIO_SPI_0 port.



2.7 GPIO Multiplexing

Table 14. GPIO Multiplexing

GPIO No.	Signal Name	Process or Pin No.	Community	Community Offset	I/O Voltage	Default Termination	Buffer Type	Default Mode	Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6
GPIO_20	GPIO_20	B27	N	320	1.8 V	20K PD	HSMV	GP-In	RSVD	RSVD	RSVD	RSVD	IERR	0
GPIO_21	GPIO_21	C26	N	336	1.8 V	20K PD	HSMV	GP-In	RSVD	RSVD	RSVD	RSVD	MCERR	0



2.8

RTC Signals

In addition to the internal RTC oscillator, an optional mode is available to supply the RTC clock from an external source. In this case, an oscillator or a single clock output can be used to drive into X1 with X2 left as no contact. Contact your Intel representative for more information.

Table 15. RTC Signals

Signal Name	Dir.	I/O Voltage	Type	Description
RTC_X1	I	NA	RTC PHY	Crystal Input 1: This signal is connected to a 32.768 kHz crystal (max 50kΩ ESR). If using an external oscillator, the RTC_X1 Vih must be within the range of 0.8V to 1.5V (1.5V max) and Vil must be within range of -0.2V to 0.2V (0.2V max).
RTC_X2	O	NA	RTC PHY	Crystal Input 2: This signal is connected to a 32.768 kHz crystal (max 50kΩ ESR). If using an external oscillator, RTC_X2 should be left floating.

2.9

Other Signals

Other signals that are not mentioned in this document, such as Digital Display Interface and SVID, have the same names as those in Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3 (Document Number: 334817).

§

3.0 Functional Description

3.1 Processor Core Overview

The processor core for Intel Atom® processor E3900 and A3900 series (formerly Apollo Lake-II) is the same as the processor core for Intel® Pentium® and Celeron® Processor N- and J- Series (formerly Apollo Lake). Figure 2 and Figure 3 show the CPU L2 Cache structure for the dual-core processor and the quad-core processor, respectively.

Note: L1 cache has Parity Protection and L2 cache has ECC Protection.

Figure 2. CPU L2 Cache Structure (Dual Core)





Figure 3. CPU L2 Cache Structure (Quad Core)





3.2 System Memory Controller

3.2.1 Supported Memory Overview

The processor Integrated Memory Controller (IMC) supports the following memory technologies on two independent 64-bit (72-bit for ECC) channels.

Table 16. Supported Memory Technologies

Technology Attributes	LPDDR4	DDR3L	DDR3L ECC
Channels	Up to 4 (x32)	Up to 2 (x64)	Up to 2 (x72)
Peak Bandwidth (GB/s)	Up to 38.4	Up to 29.86	Up to 25.6
Maximum Data Transfer Rate (MT/s)	NOTE	NOTE	1333/1600
Maximum Total System Capacity	NOTE	NOTE	8 GB
Raw Card Support	NOTE	NOTE	C(1Rx8) D(2Rx8)
Densities (Gb)	NOTE	NOTE	4, 8
CMD/Adds pins per channel	NOTE	NOTE	16
DQ pins per channel	NOTE	NOTE	72
Voltage Rail (V)	NOTE	NOTE	1.35
Scrambling	Yes		
On Die Termination Control	Yes		
Same Rank Interleaving	Yes		
Refresh	No per bank-refresh, only at rank level		
Power-Saving Features	Fast Exit Power Down, Self-Refresh plus extra features, Power/Trunk gating		

NOTE: Same as the N- and J- Series Processors.



3.2.2

Memory Configurations

For further information, refer to the Memory Configurations section in Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3 (Document Number: 334817). Disregard the LPDDR3 contents; they are not supported by E3900 and A3900 series processors.

3.3

SDIO

The processor has an integrated SDIO controller, which implements the following features.

Note: SD cards are not supported by this interface.

Table 17. SDIO Features

Category	Feature Supported
Specification	Supports SDIO Specification Version 3.00
Data Rate	Supports up to 100 MB/s data rate using 4 parallel data lines (SDR104 modes)
Transfer Modes	Supports transfer data in 1-bit and 4-bit SD modes
Mode of Operation	Supports both ADMA2/DMA and Non-DMA modes of operation
Cyclic Redundancy Check	Supports CRC7 for command and CRC16 for data integrity
Others	<ul style="list-style-type: none">• Supports Async Interrupt Cards• Supports in-band wake during S0• Supports Interrupt Coalescing

Table 18. SDIO Working Modes

SDIO Mode	Data Rate	Maximum Clock Frequency	Maximum Data Throughput
SDR12	Single	25 MHz	2.5 MB/s
SDR25	Single	50 MHz	25 MB/s
SDR50	Single	100 MHz	50 MB/s
DDR50	Dual	50 MHz	50 MB/s
SDR104	Single	200 MHz	100 MB/s



3.4 Audio Controller

Table 19. Audio Controller Features

Category	Description
I2S/SSP Interfaces	Six I ² S/SSP interfaces for platform peripherals
DSPs	Two high-performance DSPs configured with: <ul style="list-style-type: none"> • 32kB 4-way set associative L1 Instruction Cache • 64kB 4-way set associative L1 Data Cache
L2	<ul style="list-style-type: none"> • L2 memory controller with the local high-performance interconnect fabric • L2 cache controller with caching and prefetch capabilities
ROM Size	8kB ROM
DMA Interfaces	Two 8-channel universal DMA interfaces to transfer data between memory buffers and peripherals, and between memories
DMIC Interfaces	Two dual-channel DMIC interfaces
Intel® High Definition Audio (Intel® HD Audio) and LPE Audio	Supports Intel® HD Audio and LPE Audio for DDI [1:0]: DisplayPort* and High Definition Multimedia Interface (HDMI*)
CODEC	Supports one external CODEC for attaching audio peripherals
Burst Mode	Local power sequencer for burst-mode data processing in micropower modes (S0ix)
Debug Interface	DSP On-chip Debug interface with two JTAG ports

3.5 Serial I/O (SIO) (LPSS)

Table 20. I/O Supported Interfaces

Interface	Number of Ports	Maximum Speed
[SIO] I ² C*	8	3.1 Mb/s
[SIO] HSUART	4	115,200 kb/s (standard 16550) 3.6864 Mb/s (high-speed 16750)
[SIO] SPI	3	25 Mb/s



3.6 Clocking

Table 21. Summary of Clock Signals

Interface	Clock Signal	Clock Frequency
Memory - DDR3L	NOTE	NOTE
Memory - LPDDR4	NOTE	NOTE
PCIe*	NOTE	NOTE
Storage - eMMC* 4.51 and 5.0	NOTE	NOTE
Storage - SD Card	NOTE	NOTE
Storage - SDIO	SDIO_CLK	25, 50, 100, 200 MHz
Display - DisplayPort, HDMI	NOTE	NOTE
Display - MIPI*-DSI	NOTE	NOTE
Camera - MIPI-CSI	NOTE	NOTE
Audio - Intel® HD Audio	NOTE	NOTE
Audio Codec/Analog Microphone - I2S	AVS_I2S[1:6]_BCLK AVS_I2S[1:2]_MCLK	BCLK = <programmable> MCLK = <programmable>
Audio - Digital Microphone	NOTE	NOTE
SIO (LPSS) I ² C	NOTE	NOTE
PMIC	NOTE	NOTE
SVID	NOTE	NOTE
LPC	NOTE	NOTE
SMBus	NOTE	NOTE
SIO (LPSS) SPI	SIO_SPI_[0:2]_CLK	25 MHz
FAST SPI - SPI NOR and TPM	NOTE	NOTE
SPI	NOTE	NOTE
Platform - OSC_CLK_OUT	NOTE	NOTE
Platform - SUSCLK	NOTE	NOTE
XTAL Source - RTC Clock	NOTE	NOTE
XTAL Source - Processor Clock - as default	NOTE	NOTE

NOTE: Same as the N- and J- Series Processors.



3.7

Spread Spectrum Clocking for EMI mitigation

Spread Spectrum Clocking for Electrical Magnetic Interference is supported in Apollo Lake -I, up to a maximum down-spread amplitude of 0.5%. The components affected by SSC are the following:

- DDR Memory
- HSIO interfaces (USB3, PCIe, eDP, DP, eMMC, SD Card and SDIO)

3.8

Other Interfaces

For other interfaces that are not mentioned in this document, such as display controller, graphics and media engine, refer to Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3 (Document Number: 334817).

§



4.0 Electrical Specifications

Table 22 lists the Power Rail DC specifications and ICCMAX for the processor. Table 25 lists the DC specifications for SDIO. Refer to Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3 (Document Number: 334817) for other electrical specifications.

4.1 Voltage and Current Specifications

Table 22. Power Rail DC Specifications and ICCMAX Values

Power Type	Voltage Range (V)	Voltage Tolerance (AC+DC+Ripple)	Power Well Description	I _{CCMAX} (A)
VCC_VCGI	NOTE	With AVP: (NOTE)	NOTE	Refer to Table 2 and Table 4
		Without AVP: (NOTE)		
VNN_SVID	NOTE (DDR3L)	NOTE	NOTE	4.4
	NOTE (LPDDR4)	NOTE	NOTE	2.9
VCCIOA	NOTE	NOTE	NOTE	Included in either VNN_SVID (DDR3L) or VDDQ (LPDDR4)
VCCRAM_1P05	NOTE	NOTE	NOTE	NOTE
VCCRAM_1P05_IO	NOTE	NOTE	NOTE	
VCC_1P05_INT	NOTE	NOTE	NOTE	
VDD2_1P24_GLM	NOTE	NOTE	NOTE	NOTE
VDD2_1P24_AUD_ISH_PLL	NOTE	NOTE	NOTE	
VDD2_1P24_MPHY	NOTE	NOTE	NOTE	
VDD2_1P24_USB2	NOTE	NOTE	NOTE	
VDD2_V1P24_DSI_SI	NOTE	NOTE	NOTE	
VCC_1P8V_A	NOTE	NOTE	NOTE	
VDDQ	NOTE (DDR3L)	NOTE	NOTE	2.8
	NOTE (LPDDR4)	NOTE	NOTE	4.3



Power Type	Voltage Range (V)	Voltage Tolerance (AC+DC+Ripple)	Power Well Description	I_{CCMAX} (A)
VCC_3P3V_A	NOTE	+5%-6.5%	NOTE	NOTE
VCC_RTC_3P3V	3.3 (coin battery backed)	NOTE	NOTE	2 m (S0 state) 6 μ (G3 state)

NOTE: Same as the N- and J- Series Processors.

Table 23. Intel Atom® Processor E3900 Series V_{CC_VCGI} Rail I_{CCMAX} Values

SKU Name	I _{CCMAX} (A)
E3950	16
E3940	15
E3930	10.5

Table 24. Intel Atom® Processor A3900 Series V_{CC_VCGI} Rail I_{CCMAX} Values

SKU Name	I _{CCMAX} (A)
A3960	21
A3950	16
A3940	15
A3930	10.5
A3920	16

4.2 SDIO DC Specifications

Table 25. SDIO Signal Group DC Specifications

Symbol	Parameter	Minimum Value	Maximum Value	Unit	Notes
VCC	I/O voltage	1.66	1.89	V	1.8 V nominal
VOH	Output high voltage	1.35	-	V	At 1.80 V nominal (Vcc- 0.45), at 3 mA load
VOL	Output low voltage	-	0.45	V	At -3 mA load



Electrical Specifications

Symbol	Parameter	Minimum Value	Maximum Value	Unit	Notes
VIH	Input high voltage	1.17	-	V	At 1.80 V nominal (0.65xVcc)
VIL	Input low voltage	-	0.63	V	At 1.80 V nominal (0.35xVcc)
CL	Bus signal line capacitance	-	5	pF	-
IPAD	Pad leakage current	-5	5	µA	-
ZUP	Driver pull-up impedance	32	48	Ω	40 Ω nominal
ZDN	Driver pull-down impedance	32	48	Ω	40 Ω nominal
Wpup20K	Weak pull-up impedance 20 K	8	44	kΩ	20 kΩ nominal
Wpdn20K	Weak pull-down impedance 20 K	8	44	kΩ	20 kΩ nominal
Vhys	RX hysteresis	100	-	mV	-
Cin	Pad capacitance	-	5	pF	-
VOS	Overshoot voltage magnitude [time duration for 200 MHz < 0.4 ns]	-	2.15	V	(1), (2)
VUS	Undershoot voltage magnitude [time duration for 200 MHz < 0.4 ns]	-	-0.35	V	(1), (2)
VOS	Overshoot voltage magnitude [time duration for 200 MHz < 0.8 ns]	-	-0.35	V	(1), (2)
VUS	Undershoot voltage magnitude [time duration for 200 MHz < 0.8 ns]	-	2.1	V	(1), (2)

Electrical Specifications

Symbol	Parameter	Minimum Value	Maximum Value	Unit	Notes
VOS	Overshoot voltage magnitude [time duration for 200 MHz < 1.25 ns]	-	-0.3	V	(1), (2)
VUS	Undershoot voltage magnitude [time duration for 200 MHz < 1.25 ns]	-	2.06	V	(1), (2)

NOTES:

1. Activity Factor = 0.25, that is, one out of four received cycles has the VOS/VUS.
2. $T_j = 105^\circ\text{C}$

§



5.0 Ball Map, Processor Pin Locations, and Package Information

Table 26 compares the signal names of the N- and J- Series Processors to those of the E3900 and A3900 Series Processors. Refer to Intel® Pentium® and Celeron® Processor N- and J- Series Datasheet Volume 1 of 3 (Document Number: 334817) for other processor pin names.

Table 26. Signal Name Comparison between N- and J- Series Processors and E3900 and A3900 Series Processors

PIN Number	N- and J- Series Processors	E3900 and A3900 Series Processors
AW48	NCTF	MEM_CH0_ECC_DQ0 ^(NOTE)
AW47	NCTF	MEM_CH0_ECC_DQ1 ^(NOTE)
BB43	NCTF	MEM_CH0_ECC_DQ2 ^(NOTE)
AW45	NCTF	MEM_CH0_ECC_DQ3 ^(NOTE)
AV48	NCTF	MEM_CH0_ECC_DQ4 ^(NOTE)
AV47	NCTF	MEM_CH0_ECC_DQ5 ^(NOTE)
BD43	NCTF	MEM_CH0_ECC_DQ6 ^(NOTE)
BA45	NCTF	MEM_CH0_ECC_DQ7 ^(NOTE)
BD47	NCTF	MEM_CH0_ECC_DQS_P ^(NOTE)
BB47	NCTF	MEM_CH0_ECC_DQS_N ^(NOTE)
AR21	NCTF	MEM_CH1_ECC_DQ0 ^(NOTE)
AT21	NCTF	MEM_CH1_ECC_DQ1 ^(NOTE)
AW23	NCTF	MEM_CH1_ECC_DQ2 ^(NOTE)
AW21	NCTF	MEM_CH1_ECC_DQ3 ^(NOTE)
BA19	NCTF	MEM_CH1_ECC_DQ4 ^(NOTE)
AW19	NCTF	MEM_CH1_ECC_DQ5 ^(NOTE)
BA23	NCTF	MEM_CH1_ECC_DQ6 ^(NOTE)
BB23	NCTF	MEM_CH1_ECC_DQ7 ^(NOTE)
BD23	NCTF	MEM_CH1_ECC_DQS_P ^(NOTE)
BE23	NCTF	MEM_CH1_ECC_DQS_N ^(Note)
P58	GPIO_166	SDIO_CLK




PIN Number	N- and J- Series Processors	E3900 and A3900 Series Processors
T52	GPIO_167	SDIO_D0
P57	GPIO_168	SDIO_D1
T54	GPIO_169	SDIO_D2
T55	GPIO_170	SDIO_D3
T57	GPIO_171	SDIO_CMD
P51	GPIO_183	SDIO_PWR_DWN_N

NOTE: Applicable to the DDR3L ECC option only



5.1

Package Mechanical Drawing: Apollo Lake-I¹Figure 4. Package Mechanical Drawing: Apollo Lake-I¹(1 of 2)


Intel Atom® Processor E3900 & A3900 Series

Note:

- Between lowest active temperature of the board paste to peak reflow temperature.



Figure 5. Package Mechanical Drawing: Apollo Lake-I¹ (2 of 2)



§