





### Breakthrough Compute Architecture

Intel® Xeon® W-3400 and Xeon® W-2400 processors represent an architectural turning point in power and scalability for professional high-end compute needs. These processors bring a breakthrough in advanced CPU packaging technology featuring Embedded Multi-die Interconnect Bridge (EMIB) technology which elegantly connects multiple heterogeneous die in a single solution, alleviating processing bottlenecks and enabling up to 56 cores in a single socket. This gives professionals double the core counts over the previous leading generation of Intel® Xeon® W-3400 and Xeon® W-2400 processors to

manage to manage compute-intensive, highly threaded workflows. At the same time, CPU speeds of up to 4.8 GHz with Intel® Turbo Boost Max Technology 3.0 optimize core performance on-demand for lightly-threaded applications, increasing system responsiveness. An expanded Intel® Smart Cache of up to 105MB reduces latency in complex workloads, like code compilation or rendering, by reducing the amount of time spent swapping data between cache and memory. With this all-new compute architecture designed to optimize CPU performance across workloads, creatives, engineers, and data scientists can work at their best.











Workstations based on new Intel® Xeon® W-3400 and Xeon® W-2400 processors deliver the tools that enterprises need to integrate and manage workstation platforms within their existing networks seamlessly and securely. Boost security for virtualized environments with Intel VT-Redirect Protection (Intel® VT-rp) which offers hardware-enabled protection for the Windows kernel. With Intel® Firmware Version Control (FVC), enterprises benefit from additional system stability that prevents re-installation of older

firmware. Premier system management capabilities —including Intel® Active Management Technology, Intel® Platform Trust Technology, and Intel® Boot Guard—empower IT professionals to manage and secure their enterprise systems from wherever they are. Intel Xeon W-3400 and Xeon W-2400 processor-based workstation platforms make it easy to integrate, manage, and secure hardware and data so that enterprises can operate with peace of mind.

# INTEL® XEON® W-3400 AND INTEL® XEON® W-2400 PROCESSORS FEATURES AT A GLANCE

FEATURE	BENEFIT		
New Processor Core Architecture	Utilizes Embedded Multi-die Interconnect Bridge (EMIB) packaging technology to deliver a scalable architecture, increasing core-counts in a single socket for the next generation of workstations		
Up to DDR5 ECC RDIMM 4800 MT/s <sup>4</sup>	Delivers up to 4TB of memory support for power savings, faster memory speeds, and higher memory bandwidth		
PCIe 5.0 up to 112 Lanes	Offers readiness for up to 224 GT/s for fast access to peripheral devices and networking with up to 112 PCI Express 5.0 lanes		
Increased L2 Cache and L3 Shared Intel® Smart Cache	Up to 105MB for increased performance and data management by reducing time spent swapping data between cache and memory		
3rd Gen Intel® Deep Learning Boost <sup>1</sup>	Accelerates training and inferencing of AI models enabling developers' end-to-end workflow		
Support for select Intel vPro® Enterprise Technology²	Give IT professionals the tools for easy system integration & management of workstation platforms into existing enterprise networks		
ECC Memory Support	Error-Correcting Code memory detects and corrects errors and improves the integrity of essential data without workflow interruption		
Intel® Turbo Boost Max Technology 3.0	Identifies the processor's fastest cores and directs critical workloads to them		
Intel® Turbo Boost Technology 2.0	Intelligently boosts the processor to run faster than its rated frequency as power, heat, and workload allow		

#### INTEL® W790 CHIPSET FEATURES AT A GLANCE

FEATURE	BENEFIT		
Support for Intel® Xeon® W-3400 & Intel® Xeon® W-2400 Processors	Supports Intel® Xeon® W-3400 & Intel® Xeon® W-2400 Processors		
High Speed I/O Lanes	Up to 38 lanes for configuration flexibility and accelerated performance		
PCIe Express 3.0 Interface	Offers up to 8 GT/s for fast access to peripheral devices and networking with up to 12 PCI Express 3.0 lanes, configurable as x1, x2, and x4 depending on motherboard designs		
PCIe Express 4.0 Interface	Offers up to 16 GT/s for fast access to peripheral devices and networking with up to 16 PCI Express 4.0 lanes, configurable as x1, x2, and x4 depending on motherboard designs		
рмі	Supports faster data transfer with increased lanes of up to 8 Direct Media Interface Gen 4.0		
USB 3.2 Gen 2x2	Integrated USB 3.2 Gen 2x2 support provides data transfer performance with a design data rate of up to 20 Gb/s		
USB 3.2 Gen 2x1	Integrated USB 3.2 Gen 2x1 support provides data transfer performance with a design data rate of up to 10 Gb/s		
USB 3.2 Gen 1x1	Integrated USB 3.2 Gen 1x1 support provides data transfer performance with a design data rate of up to 5 Gb/s		
USB 2.0	High-Speed USB 2.0 support with a design data rate of up to 480 Mb/s		
Serial ATA (SATA) 6 Gb/s	High-speed storage interface supporting up to 6 Gb/s transfer rates for optimal data access		
Intel® Wi-Fi 6E Support	Integrated Intel® Wi-Fi 6E AX211(Gig+) CNVi solution or Intel® Wi-Fi 6E AX210(Gig+) solution allowing you to connect up to Gigabit Wi-Fi speeds		
Modern Manageability with Intel® Active Management Technology (Intel® AMT)	Remote out-of-band management for efficient proactive and reactive system maintenance over Ethernet or Wi-Fi connections		
Intel® Boot Guard	Supports cryptographically-verified boot as recommended by Windows best security practices		
Intel® Platform Trust Technology	Integrated Trusted Platform Module within Intel chipsets, supporting TPM 2.0 standard		

#### INTEL VPRO® ENTERPRISE TECHNOLOGY SUPPORTED AT A GLANCE

FEATURE	BENEFIT		
Intel® Firmware Version Control (FVC)	Prevents reinstallation of older firmware		
Intel® VT-rp (redirect protection) (Formerly HLAT)	Hardware-enhanced protection for OS virtualization		
Intel® Virtualization Technology (Intel® VT-x / VT-d)	Accelerates hypervisor and virtual machine switching for OS security services		
Intel® Platform Trust Technology	Integrated Trusted Platform Module within Intel SOCs, supporting TPM 2.0 and Intel® TXT		
Intel® Trusted Execution Technology (Intel® TXT)	Provides dynamic root of trust for Windows or other system software		
Intel® Control Flow Enforcement Technology (Intel® CET)	Hardware-enhanced protection against memory safety attacks, such as malicious code insertion into applications executing in PC memory		
Intel® Transparent Supply Chain (Intel® TSC)	Mechanism for confirming authenticity of system components and firmware via digital certificate, an As-Built report, and an Auto Verify Tool		
Intel® Boot Guard	Supports cryptographically-verified boot as recommended by Windows best security practices		
Intel® BIOS Guard	Helps protect firmware residing in non-volatile memory		
Intel's Advanced Programmable Interrupt Controller with Virtualization (APIC-v)	Provides hardware support for task switching including hypervisors and Virtualization-Based Security (VBS) in Windows* 10		
Intel® Active Management Technology (Intel® AMT)	Remote out-of-band management for efficient proactive and reactive system maintenance over Ethernet or Wi-Fi connections		
Intel® Endpoint Management Assistant (Intel® EMA)	Provides the ability to remotely and securely manage Intel® Active Management Technology (Intel® AMT) devices beyond the firewall		
Intel® Unique Platform ID (Intel® UPID)	Creates unique and persistent ownership credentials for Intel vPro® devices to facilitate deployment of services		

intel.

intel.

#### INTEL® XEON® W-3400 PROCESSORS COMPARISON

Intel® Advanced Vector Extensions 512 (Intel® AVX-512)

Intel® Advanced Vector Extensions 512 (Intel® AVX-512) FMA Units intel.


	Xeon	Xeon	Xeon
	w9	w7	w5
	Intel® Xeon® w9	Intel® Xeon® w7	Intel® Xeon® w5
Processor Cores	Up to 56 (56P+0E)	Up to 28 (28P+0E)	Up to 16 (16P+0E)
Intel® Hyper-Threading Technology	Yes		
Total Processor Threads	Up to 112	Up to 56	Up to 32
Intel® Smart Cache (L3)	Up to 105MB	Up to 75MB	Up to 45MB
Intel® Turbo Boost Max Technology 3.0 Frequency (GHz)	Up to 4.8		Up to 4.7
Processor Base Frequency	Up to 2.2	Up to 2.6	Up to 3.2
CPU PCIe 5.0 Lanes	112		
Mamimum Memory Speed (MT/s)	DDR5 4800 <sup>2</sup>		
Memory Channels			
Maximum Memory Capacity <sup>2</sup>	4TB		
Maximum Turbo Power (W)	Up to 420	Up to 360	up to 324
Processor Base Power (W)	Up to 350	Up to 300	Up to 270
Realiability, Availability & Serviceability		ECC, Standard RAS	
Intel vPro® Enterprise Technology <sup>6</sup>	Yes		
Intel® Boot Guard	Yes		
Intel® Platform Trust Technology	Yes		
3rd Gen Intel® Deep Learning Boost	Yes		
Intel® Data Streaming Accelerator (Intel® DSA)	Yes		
Intel® Advanced Matrix Extensions (Intel® AMX)	Yes		
Intel® Advanced Vector Extensions 2 (Intel® AVX2)	Yes		

### INTEL® XEON® W-2400 PROCESSORS COMPARISON


w7	w ender
xeon xeon	хеон
intel. intel.	intel.

	Intel® Xeon® w7	Intel® Xeon® w5	Intel® Xeon® w3	
Processor Cores	Up to 24 (24P+0E)	Up to 16 (16P+0E)	Up to 8 (8P+0E)	
Intel® Hyper-Threading Technology	Yes			
Total Processor Threads	Up to 48	Up to 32	Up to 16	
Intel® Smart Cache (L3)	Up to 45MB	Up to 33.75MB	Up to 22.5MB	
Intel® Turbo Boost Max Technology 3.0 Frequency (GHz)	Up to 4.8	Up to 4.7	Up to 4.5	
Processor Base Frequency	Up to 2.6	Up to 3.2	Up to 3.1	
CPU PCIe 5.0 Lanes	64			
Mamimum Memory Speed (MT/s)	DDR5 4800²		DDR5 4400 <sup>7</sup>	
Memory Channels				
Maximum Memory Capacity <sup>2</sup>	2ТВ			
Maximum Turbo Power (W)	270	Up to 240	Up to 198	
Processor Base Power (W)	225	Up to 200	Up to 165	
Realiability, Availability & Serviceability		ECC, Standard RAS		
Intel vPro® Enterprise Technology®		Yes		
Intel® Boot Guard	Yes			
Intel® Platform Trust Technology	Yes			
3rd Gen Intel® Deep Learning Boost	Yes			
Intel® Data Streaming Accelerator (Intel® DSA)	Yes			
Intel® Advanced Matrix Extensions (Intel® AMX)	Yes			
Intel® Advanced Vector Extensions 2 (Intel® AVX2)	Yes			
Intel® Advanced Vector Extensions 512 (Intel® AVX-512)	Yes			
Intel® Advanced Vector Extensions 512 (Intel® AVX-512) FMA Units				

### Intel® Xeon® W-3400 Platform Block Diagram



## Intel® Xeon® W-2400 Platform Block Diagram



#### Platform Brief Intel® Xeon® W-3400 & Intel® Xeon® W-2400 Processors | Intel® W790 Chipset

Notices & Disclaimers

Performance varies by use, configuration and other factors. Learn more at <a href="https://www.intel.com/PerformanceIndex">www.intel.com/PerformanceIndex</a>

Performance results are based on testing as of dates shown in configurations and may not reflect all publicly available updates. See backup for configuration details. No product or component can be absolutely secure.

All versions of the Intel vPro® platform require an eligible Intel® Core™ processor, a supported operating system, Intel LAN and/or WLAN silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance and stability that define the platform. See www.intel.com/Performance-vPro for details.

For more information, please visit intel.com/workstation

- 1.3rd Generation Intel Deep Learning boost consists of AVX-512, TMUL, and Bfloat16 instruction sets.
- 2.For a full list of Intel vPro platform technologies by product line visit https://www.intel.com/content/www/us/en/products/details/processors/vpro.html
- 3.Compared to previous generation workstation platforms, Xeon W-3200 with 6 channels of DDR4 RDIMM Memory Support.
- 4.Maximum memory speeds are associated with 1 DIMM per Channel (1DPC) configurations. Additional DIMM loading on any channel may impact maximum memory speed. Maximum memory capacity is achievable with 2DPC configurations.
- 5.Overclocking Disclaimer: Unlocked features are present with select chipsets and processor combinations. Altering clock frequency or voltage may void any product warranties and reduce stability, security, performance, and life of the processor and other components. Check with system and component manufacturers for details.
- 6.Intel vPro® Enterprise with Intel® Active Management Technology (Intel® AMT) or Intel® Standard Manageability (Intel® ISM) when paired with a motherboard with supporting hardware and software, and potential service activation.
- 7. DDR5 4400 MT/s memory speed supported with 1DPC and 2DPC configurations.
- \*Other names and brands may be claimed as the property of others.

